

### **BLANK PAGE**



IS: 3347 (Part 4/Sec 1) - 1988

#### Indian Standard

REAFFIRMED APR2004

# DIMENSIONS FOR PORCELAIN TRANSFORMER BUSHINGS FOR USE IN LIGHTLY POLLUTED ATMOSPHERES

PART 4 24 kV BUSHINGS

Section 1 Porcelain Parts

(Second Revision)

First Reprint AUGUST 1994

UDC  $621 \cdot 315 \cdot 626$   $[621 \cdot 315 \cdot 612 \cdot 2]$  :  $621 \cdot 314 \cdot 1/ \cdot 2$  :  $006 \cdot 78$ 

© Copyright 1989

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

#### AMENDMENT NO. 1 MAY 1993 TO

### IS 3347 (Part 4/Sec 1): 1988 DIMENSIONS FOR PORCELAIN TRANSFORMER BUSHINGS FOR USE IN LIGHTLY POLLUTED ATMOSPHERES

#### PART 4 24 AND 27 kV BUSHINGS

#### Section 1 Porcelain Parts

(Second Revision)

(Page 5, Fig. 3, informal table, Dimension B) — Substitute '51' for '50'.

(ET 06)	
	Reprography Unit, BIS, New Delhi, India

#### Indian Standard

## DIMENSIONS FOR PORCELAIN TRANSFORMER BUSHINGS FOR USE IN LIGHTLY POLLUTED ATMOSPHERES

#### PART 4 24 kV BUSHINGS Section 1 Porcelain Parts

(Second Revision)

#### 0. FOREWORD

- **0.1** This Indian Standard (Part 4/Sec 1) (Second Revision) was adopted by the Bureau of Indian Standards on 24 June 1988, after the draft finalized by the Electrical Insulators and Accessories Sectional Committee had been approved by the Electrotechnical Division Council.
- **0.2** This part (Part 4) of the standard covers dimensions of porcelain transformer bushings for use in lightly polluted atmospheres with the object of ensuring their interchangeability. To avoid multiplicity of sizes, the dimensions given are only for those ratings (voltage and current) which are being used appreciably. This part comprises two sections issued as two separate standards. This section (Sec 1) covers porcelain parts of the bushings whereas the dimensions of the metal parts to go with those porcelain parts are covered in Section 2 of this standard.
- **0.3** This standard (Part 4/Sec 1) was first issued in 1965. The first revision was taken up in 1973 with a view to simplify the manufacture of the porcelain parts on large scale by permitting an alternative shape of their top petticoat in respect of all the ratings covered in this standard. This second revision has been undertaken:
  - a) to align the dimensions with current national and international practices, and
  - b) to incorporate the new classification of polluted atmospheres given in IS: 2099-1986\*.
- **0.4** The dimensions given in this standard have been arrived at after full consideration of the available sizes and an examination of the relevant merits of different types of bushings. Detailed dimensions have been given with a view to achieving maximum economy in the manufacture of the bushings.
- **0.5** The bushings are rated in terms of the highest system voltage (*see* IS : 2099-1986\*). The

dimensions of the bushings for other voltages are given in following parts of this standard:

IS: 3347 Dimensions for porcelain transformer bushings for use in lightly polluted atmospheres:

- Part 1 Up to and including 1 kV Section 1 Porcelain parts Section 2 Metal parts
- Part 2 3.6 kV bushings
  Section 1 Porcelain parts
  Section 2 Metal parts
- Part 3 17.5 kV bushings
  Section 1 Porcelain parts
  Section 2 Metal parts
- Part 5 36 kV bushings
  Section 1 Porcelain parts
  Section 2 Metal parts
- Part 6 72.5 kV bushings
  Section 1 Porcelain parts
  Section 2 Metal parts
- Part 7 123 kV bushings
  Section 1 Porcelain parts
  Section 2 Metal parts
- Part 8 52 kV bushings
  Section 1 Porcelain parts
  Section 2 Metal parts

  Preparation
- **0.6** The dimensions for porcelain transformer bushings for use in heavily polluted atmospheres are covered by the series of IS: 8603-1977\*.
- **0.7** The dimensions covered in this standard essentially apply to the bushings used outdoor with lower ends immersed in oil and suitable for use in lightly polluted atmospheres.

<sup>\*</sup>Specification for bushings for alternating voltages above 1 000 volts (second revision).

<sup>\*</sup>Dimensions for porcelain transformer bushings for use in heavily polluted atmospheres.

#### IS: 3347 (Part 4/Sec 1) - 1988

- **0.8** The performance requirements of the bushings are specified in IS: 2099-1986\*.
- **0.9** In the preparation of this standard, assistance has been derived from the following standards issued by the Deutsches Institut für Normung.
  - DIN 42531 (1968) Indoor and outdoor transformer bushings:

Insulation class 10 N to 30 N, 250 A.

DIN 42532 (1969) Indoor and outdoor transformer bushings:

Insulation class 10 N to 30 N, 630 A.

DIN 42533 (1969) Indoor and outdoor transformer bushings:

Insulation class  $10\ N$  to  $30\ N$ ,  $1\ 000$  to  $3150\ A$ .

**0.10** For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS: 2-1960\*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

#### 1. SCOPE

**1.1** This standard (Part 4/Sec 1) lays down the dimensions of porcelain parts of the bushings of 24 kV class used with transformers for use in lightly polluted atmospheres.


#### 2. DIMENSIONS

**2.1** The dimensions of the porcelain bushings for different ratings (kV/A) are given in Fig. 1, 2 and 3.

- **2.2** Unless specified otherwise, tolerance on a dimension shall be  $\pm (0.03 \ d + 0.3) \ mm, d$  being the dimension in millimetres.
- **2.3** Whenever unilateral tolerance is given, that tolerance shall be twice the general tolerance, for example, dimension  $X_{\text{max}}$ , shall have twice the general tolerance given in 2.2 for lower dimensions and no tolerance on upper dimension.
- **2.4** The minimum specific creepage distance shall be 384 mm (16 mm/kV).


<sup>\*</sup>Specification for bushings for alternating voltages above 1 000 volts (second revision).

<sup>\*</sup>Rules for rounding off numerical values (revised).



All dimensions in millimetres.

FIG. 1 PORCELAIN PART FOR 24 kV/250 A BUSHINGS



All dimensions in millimetres.

FIG. 2 PORCELAIN PART FOR 24 kV/630 A BUSHINGS

#### AMENDMENT NO. 1 MAY 1993 TO

## IS 3347 (Part 4/Sec 1): 1988 DIMENSIONS FOR PORCELAIN TRANSFORMER BUSHINGS FOR USE IN LIGHTLY POLLUTED ATMOSPHERES

#### PART 4 24 AND 27 kV BUSHINGS


Section 1 Porcelain Parts

(Second Revision)

(Page 5, Fig. 3, informal table, Dimension B)—Substitute '51' for '50'.

(ET 06)

Reprography Unit, BIS, New Delhi, India



All dimensions in millimetres.

RATIMG kV/A	A	В	С	D	D1	E	F	G	Н	K	M	N	S	T
24/1 000	163 <sup>+0</sup> <sub>-10</sub>	32	58 <sup>+4</sup> <sub>-0</sub>	80	84 +0	100	105	110	108 <sup>+0</sup> - 7	175	180	185	12	46
24/2 000, 3 150	183 <sup>+0</sup>	50	74 <sup>+5</sup> <sub>-0</sub>	100	104 <sup>+0</sup> - 7	125	120	130	131 <sup>+0</sup> <sub>-8</sub>	190	200	210	17	62

FIG. 3 PORCELAIN PART FOR 24 kV/1 000, 2 000, 3 150 A BUSHINGS

#### **Bureau of Indian Standards**

**BIS** is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

#### Copyright

**BIS** has a copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of **BIS**. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

#### **Review of Indian Standards**

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such a review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Handbook' and 'Standards Monthly Addition'.

#### **Amendments Issued Since Publication**

Amend No.	Date of Issue	Text Affected				
		· · · · · · · · · · · · · · · · · · ·				

#### BUREAU OF INDIAN STANDARDS

#### **Headquarters:**

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 11000
--

Telephones: 331 01 31, 331 13 75	Telegrams : Manaksanstha (Common to all Offices)
Regional Offices:	Telephones
Central: Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	<b>{</b> 331 01 31 331 13 75
Eastern: 1/14 C.I.T. Scheme VII M, V.I.P. Road, Maniktola CALCUTTA 700054	<b>{</b> 37 84 99, 37 85 61 37 86 26, 37 86 62
Northern: SCO 445-446, Sector 35-C, CHANDIGARH 160036	<b>{</b> 53 38 43, 53 16 40 53 23 84
Southern: C.I.T. Campus, IV Cross Road, MADRAS 600113	{ 235 02 16, 235 04 42 235 15 19, 235 23 15
Western: Manakalaya, E9 MIDC, Marol, Andheri (East) BOMBAY 430093	{ 632 92 95, 632 78 58 632 78 91, 632 78 92

Branches: AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. LUCKNOW. PATNA. THIRUVANANTHAPURAM.